



Italiana Parquet

PRODUCT DATA SHEET
CONTRACT PRATICA collection

Specification

GENERAL

Type of floor

Type of wood

Grading

Surface finishing

Staining available

Pattern

Locking system

Core

Hardened wood

European Oak

Blend *

Pro matt lacquer **

**PR07 (Natural), PR08 (Misty white), PR09 (Terra),
PR10 (Grey), PR11 (White)**

Plank M

5G Dry

HDF

DIMENSIONS

Format

Width

Width (ISO 24337)

Length

Length (ISO 24337)

Thickness / Thickness (ASTM F387)

Thickness of wear layer / Thickness of wear layer (ASTM F410)

M

151 mm

5.94"

2.000/2.020 mm

78.74"

9 mm / 0.35"

0,6 mm / 0.024"

PACKAGE

Quantity in box

m² / box _ sq.ft per box

m² per pallet / sq.ft per pallet

Weight per m²

Weight per box

7

2,10 m² / 22.8 sqft

95,13 m² / 1026 sqft

9 kg / 19.9 lbs

19,10 kg / 42 lbs

CLASSIFICATION AND SAFETY

Supports underfloor heating

Water resistance

Fire resistance (EN 13501)

Thermal conductivity

Thermal resistance (EN 12667)

Formaldehyde emission (EN 717-1)

Yes

High

Cfl-s1

0,12 W/(m*K)

0,075 (m² x K)/W

E1 <= 0.1 ppm (typical value <= 0.05 ppm)

Italiana Parquet S.r.l.

Via Brodolini, 26 A/B
60044 Fabriano (AN) - Italy

Tel. +39 0732 629262
info@italianaparquet.it

www.italianaparquet.it

Cod. Fisc. e PIVA 02734750413
Reg. Impr. Marche 02734750413
REA AN - 270630
Cap. sociale € 100.000,00 i.v.
PEC italianaparquet@legalmail.it
Cod.Univoco A4707H7

Società soggetta a direzione
e coordinamento di
Margaritelli S.p.a.
Sede legale fraz. Miralduolo
06089 Torgiano (PG) - Italy
Cod. Fisc. 02981200542
REA PG - 255267



Italiana Parquet

Brinell hardness (EN 1534)

Impact resistance (EN 14354)

Thickness swelling (EN 14354)

Wear resistance (EN 14354)

Slip resistance (USRV) (CEN//TS 15676)

FSC

SundaHus

A+

M1

CE marked

Level of use domestic (EN ISO 10874)

Level of use commercial (EN ISO 10874)

8 HB (average value)

EC3

<10% (5% typical)

> 6.000 cycles

40

FSC mix

Evaluated by SundaHus

Yes

Yes

Yes

Class heavy residential (Class 23)

Class heavy commercial (Class 33) **

* The Blend grading, which includes some color variations, gives it character.

** Made from FSC-certified European oak, this Class 33 product is extremely durable and ideal for high-traffic environments such as hotels, shops, offices, and cafes, or even for home entrances. The matte lacquered finish makes maintenance easy and protects the floor from stains.

For installation and maintenance instructions and further product information, contact our sales office or write to info@italianaparquet.it



Residential (domestic and residential environments)

Class 23

Heavy use: areas subject to heavy use



Commercial (commercial and public spaces)

Class 33

Heavy use: high traffic areas



Italiana Parquet reserves the right to make technical, dimensional, and aesthetic changes to the products offered, as well as to eliminate or replace certain items. This does not constitute the right of the committee to re-order the eliminated or modified products.

Rev. 12.02.2026

Italiana Parquet S.r.l.

Via Brodolini, 26 A/B
60044 Fabriano (AN) - Italy

Tel. +39 0732 629262
info@italianaparquet.it

www.italianaparquet.it

Cod. Fisc. e PIVA 02734750413
Reg. Impr. Marche 02734750413
REA AN - 270630
Cap. sociale € 100.000,00 i.v.
PEC italianaparquet@legalmail.it
Cod.Univoco A4707H7

Società soggetta a direzione
e coordinamento di
Margaritelli S.p.a.
Sede legale fraz. Miralduolo
06089 Torgiano (PG) - Italy
Cod. Fisc. 02981200542
REA PG - 255267