



Italiana Parquet

TECHNICAL DATA SHEET _ ITALIANA PARQUET _ MAINTENANCE TONICO

Water-based natural oil-wax solution designed to nourish and protect wooden floors with oiled or natural oil finishes. It helps preserve over time the protection and uniform appearance of surfaces subjected to foot traffic and general use.

Instructions for use

When the floor begins to show widespread signs of wear, especially in high-traffic areas, and cleaning with **Sapone Bio** Italiana Parquet is no longer sufficient to restore its usual uniform appearance, the application of **Tonico** Italiana Parquet is recommended.

Before carrying out this treatment, it is always necessary to thoroughly wash the floor with **Sapone Bio** Italiana Parquet used at double dosage, following the instructions provided in the **Sapone Bio** technical data sheet.

For correct application of **Tonico** Italiana Parquet, ensure that the room temperature is above 15°C (59°F).

If the ambient temperature exceeds approximately 25°C (77°F), or in the presence of strong ventilation or direct sunlight exposure, the product may dry more quickly and require greater care during application.

Shake the bottle well (until any deposits are completely dissolved).

On a dry floor, apply pure **Tonico** Italiana Parquet along the length of the boards, spreading a thin and even layer using the Italiana Parquet microfiber cloth (or alternatively, a soft cloth that does not release fibers when in contact with the surface) attached to a broom. For small surfaces, surface leveling can also be carried out by hand (without using a broom).

Do not apply excessive amounts of **Tonico** Italiana Parquet, as excess product penetrating into brushed textures may be difficult to remove. After application, the surface should appear slightly wet. After approximately 1–2 hours, the floor will be dry and walkable. Subsequent washing should not be carried out before approximately 2 days have passed.

Application of **Tonico** Italiana Parquet as described above directly restores the correct surface uniformity; therefore, polishing or additional surface treatments are not necessary.

As a general guideline, the product should be applied approximately every 6 months. However, treatment becomes necessary whenever the parquet surface begins to show signs of depletion, dryness, reduced liquid resistance, or a tendency to retain dust and dirt.

In environments with medium to high traffic density, more frequent maintenance is recommended.

1 liter of product is sufficient to apply one coat on approximately 25–30 m² of surface area.

Store the product tightly closed in its original packaging, in a cool place, protected from frost and UV rays.

Never use liquids containing significant acidic or alkaline concentrations, such as ammonia or bleach, as their aggressive nature may cause permanent stains or marks on the wood.

Never use water alone for cleaning floors: besides being ineffective for proper cleaning, mineral residues contained in water may deposit on the surface and alter its reflectance.

The product is not classified as hazardous or flammable. However, it is recommended to keep it out of the reach of children.

The instructions provided in this technical data sheet are based on the Company's research and direct experience and are generally valid, given the impossibility of foreseeing all environmental and application variables.

Rev. 12.02.2026

Italiana Parquet S.r.l.

Via Brodolini, 26 A/B
60044 Fabriano (AN) - Italy

Tel. +39 0732 629262
info@italianaparquet.it

www.italianaparquet.it

Cod. Fisc. e PIVA 02734750413
Reg. Impr. Marche 02734750413
REA AN - 270630
Cap. sociale € 100.000,00 i.v.
PEC italianaparquet@legalmail.it
Cod.Univoco A4707H7

Società soggetta a direzione
e coordinamento di
Margaritelli S.p.a.
Sede legale fraz. Miralduolo
06089 Torgiano (PG) - Italy
Cod. Fisc. 02981200542
REA PG - 255267